



**Address:**  
**JAMBU PERSHAD & SONS**  
6275/22 Nicholson Road,  
Ambala Cantt, Haryana,  
INDIA  
Pin: 133001

**Email:**  
sales@japson.com  
japsonambala@yahoo.com

**Website:**  
www.japson.com  
**Phone:**  
+91-171-4006897

---

# Deluxe Water & Soil Analysis Kit

## Product Image

---



## Description

---

Catalog No : 100131

Deluxe Water & Soil Analysis Kits - Model 60, Model 61 & Model 62

# PARAMETERS

	59	60	61	62
pH	✓	✓	✓	✓
Cond.	✓	✓	✓	✓
TDS	✓	✓	✓	✓
DO	✓	✓	✓	
mV (ORP)	✓		✓	✓
Salinity	✓	✓	✓	
Turbidity		✓		
Temp.	✓	✓	✓	✓

# SPECIFICATIONS

Model	M 59	M 60	M 61	M 62
Product	µP Water & Soil Analysis Kit	Water & Soil Analysis Kit	Water & Soil Analysis Kit	Water & Soil Analysis Kit
Display	16 x 2 Characters LCD Display	3 ½ Digit LCD	3 ½ Digit LCD	3 ½ Digit LCD
<b>pH</b>				
Range	0 to 14 pH	0 to 14 pH	0 to 14 pH	0 to 14 pH
Resolution	0.01 pH	0.01 pH	0.01 pH	0.01 pH
Accuracy	0.01 ± 1 Digit	0.01 ± 1 Digit	0.01 ± 1 Digit	0.01 ± 1 Digit
Temp. Comp.	0 to 100°C(Auto/Manual)	0 to 100°C (Manual)	0 to 100°C (Manual)	0 to 100°C (Manual)
<b>Conductivity (E C)</b>				
Range	0-20, 0-200µS 0-2, 0-20, 0-200mS	0-200µS 0-2, 0-20, 0-200mS	0-20mS ---	0-20mS ---
Resolution	0.01µS/cm	0.1µS	0.01mS (10µS)	0.01mS (10µS)
Range Selection	Automatic	Manual	---	---
Accuracy	± 0.5% FS ± 1 Digit	± 0.5% FS ± 1 Digit	± 0.5% FS ± 1 Digit	± 0.5% FS ± 1 Digit
Cell Constant	Adjustable (0.05 to 10.5)	Adjustable (0.4 to 1.5)	Pre-Adjusted	Pre-Adjusted
Temp. Coefficient	Adjustable (0.4 to 4.0)	2%	2%	2%
Temp. Comp.	5-50° (Auto/Manual)	Adjustable from table	Adjustable from Table	Adjustable from Table
Reference Temp.	Selectable (5-50°C)	25°C	25°C	25°C
<b>Temperature</b>				
Range	0-100°C	0-100°C	0-100°C	0-100°C
Resolution	0.1°C	0.1°C	0.1°C	0.1°C
Accuracy	± 0.1°C ± 1 Digit	± 0.1°C ± 1 Digit	± 0.1°C ± 1 Digit	± 0.1°C ± 1 Digit
Sensor	Semi Conductor Type	Semi Conductor Type	Semi Conductor Type	Semi Conductor Type

<b>TDS</b>				
Range	0-20, 0-200ppm 0-2, 0-20, 0-200 ppt.	0-200ppm 0-2, 0-20, 0-200 ppt.	0-20 ppt	0-20 ppt
Range Selection	Automatic	Manual	---	---
Resolution	0.01 ppm	0.1 ppm	0.01ppt	0.01ppt
Accuracy	± 0.5% FS ± 1 Digit	± 0.5% FS ± 1 Digit	± 0.5% FS ± 1 Digit	± 0.5% FS ± 1 Digit
Cell Constant	Adjustable (0.05 to 10.5)	0.4 to 1.5 on display	Pre-Adjusted	Pre-Adjusted
<b>DO</b>				
Range	0-20 ppm	0-20 ppm	0-20 ppm	
Resolution	0.1 ppm	0.1 ppm	0.1 ppm	
Accuracy	0.1 ppm ± 1 Digit	0.1 ppm ± 1 Digit	0.5 ppm ± 1 Digit	
Temp. Comp.	Auto/Manual (5°C to 55°C)	Manual (5°C to 55°C)	Manual (5°C to 55°C)	
DO Sensor	Gold/Silver Probe	Gold/Silver Amperometric Probe	Gold/Silver Amperometric Probe	
<b>mV (ORP)</b>				
Range	0 to ± 1999.9 mV	0 to ± 1999 mV	---	---
Resolution	0.1 mV	1 mV	---	---
Accuracy	± 0.1 mV ± 1 digit	± 1 mV ± 1 digit	---	---
<b>Turbidity</b>				
Range	---	0-1000 JTU		
Resolution	---	1 JTU		
Accuracy	---	± 3% FS ± 1 Digit		
Sample System	---	30mm Clear Glass Tube		
<b>Salinity</b>				
Range	0-20,0-200ppm,0-2,0-20,0-50ppt	0 - 50 ppt	0 - 50 ppt	0 - 5 0 ppt
Resolution	0.01 ppm	0.1 ppt	0.1 ppt	0.1 ppt
Accuracy	± 1% of Range ± 1 Digit	± 0.5% FS ± 1 Digit	± 0.5% FS ± 1 Digit	± 0.5% FS ± 1 Digit
<b>Power Supply</b>				
	6V Rechargeable Battery or 230V±10%AC, 50Hz	1.5Vx6Dry Cells or 230V±10%AC, 50Hz	1.5Vx6Dry Cells or 230V±10%AC, 50Hz	1.5Vx6Dry Cells or 230V±10%AC, 50Hz
<b>Storage</b>				
	1000 sample	---	---	---
<b>Standard Accessories</b> pH Electrode, Cond./TDS/Salinity Cell, Temp. Probe, DO Probe, Dry Cell container (161), Main Lead, Operation Manual, Bottles for pH Solution & pH Tablets Bottles (161 & 191), Turbidity Test Tube Set (191)				

## Disclaimer

The Products details given on this page are indicative in nature and JAPSON reserves the right to change them without prior notice. Buyer is also requested to re-check the specifications and other features of product at the time of order as product development is a continuous process and minor modifications may be made to design based on latest availability, process and design.