



Address:
JAMBU PERSHAD & SONS
6275/22 Nicholson Road,
Ambala Cantt, Haryana,
INDIA
Pin: 133001

Email:
sales@japson.com
japsonambala@yahoo.com

Website:
www.japson.com
Phone:
+91-171-4006897

Digital Flame Photometer (Single Channel)

Product Image



Description

Catalog No : 100110

Digital Flame Photometer (Single Beam) - Model 65

Dual 2.5 digit bright red LED displays in (Model 66)

Measurement of 2 elements on dual LED display (Model 66 Only)

SALIENT FEATURES

- ✓ Dual Channel in Model M-66
- ✓ Stainless steel round burner
- ✓ Concentric Non-Corrosive Nebulizer
- ✓ Narrow Band interface Filters
- ✓ Dual 2½ digit red LED display
- ✓ Highly Stable & Accurate

TECHNICAL SPECIFICATIONS

- ✓ ACCURACY ± 2% up to 100 meq, ± 2% up to 40 ppm
± 5% above 100 meq, ±5% above 40 ppm
- ✓ READOUT Dual 2½ digit bright red LED displays in (Model M-66)
- ✓ IGNITION SYSTEM In-built electronic Ignition by press of a knob
- ✓ DIMENSIONS 375 X 245 X 220 mm (Approx.)
- ✓ WEIGHT 8 Kg. (Approx.)
- ✓ MEASUREMENT SYSTEM Simultaneous measurement of 2 elements on dual LED display (Model 66 Only)
- ✓ REPEATABILITY ± 2 Counts
- ✓ DETECTOR Silicon Photodiode
- ✓ FILTERS Narrow band interference glass filters
(Na, K Filters are Supplied, Ca & Li filters are optional at extra cost)
- ✓ NEBULIZER Black bakelite, axial flow type
- ✓ FLAME SYSTEM LPG and dry oil free air
- ✓ WARM UP TIME 10 minutes
- ✓ COMPRESSOR UNIT Supplied along with the instrument✓
- ✓ POWER 230V ± 10% AC, 50Hz

ACCESSORIES

- Air Compressor
- Chimney
- Sample Beakers
- Manual

Disclaimer

The Products details given on this page are indicative in nature and JAPSON reserves the right to change them without prior notice. Buyer is also requested to re-check the specifications and other features of product at the time of order as product development is a continuous process and minor modifications may be made to design based on latest availability, process and design.