



Address:
JAMBU PERSHAD & SONS
6275/22 Nicholson Road,
Ambala Cantt, Haryana,
INDIA
Pin: 133001

Email:
sales@japson.com
japsonambala@yahoo.com

Website:
www.japson.com
Phone:
+91-171-4006897

Low Viscosity Adaptor

Product Image



Description

Spindle range - 1~2K for LMDV-60
Spindle range - 0.6~6K for LMDV100
Spindle range - 0.3~6K for LMDV200
K=1000

Salient Features

- Ideal for low viscosity materials
- 20 to 30 ml sample is needed for test in Low Viscosity Adaptor (LVA30)
- Spindle Code.L0 is used with Low Viscosity Adaptor
- Stainless steel parts for easy to clean
- Especially used for less than 20m.pas. viscosity

STANDARD ACCESSORIES

1. Joint rod
2. Hook rod
3. Frame
4. Spindle Code. L0
5. Pipe

Note LVA30 is used for less than 20m.Pas viscosity measuring range.

Low Viscosity Adaptor

Catalog No. 101126

Disclaimer

The Products details given on this page are indicative in nature and JAPSON reserves the right to change them without prior notice. Buyer is also requested to re-check the specifications and other features of product at the time of order as product development is a continuous process and minor modifications may be made to design based on latest availability, process and design.