



Address:
JAMBU PERSHAD & SONS
6275/22 Nicholson Road,
Ambala Cantt, Haryana,
INDIA
Pin: 133001

Email:
sales@japson.com
japsonambala@yahoo.com

Website:
www.japson.com
Phone:
+91-171-4006897

Online pH Electrode

Product Image



Description

PE6 Online pH Electrode is designed for the measurement of the pH and temperature in aqueous solution and is suitable for continuous use in process applications.

Model	PE6
pH Range	0 to 14 pH
Temperature Sensor	NTC 10 K Ω
Operating Temperature	0 to 80°C (32 to 176°F)
Maximum Process Pressure	6 bar (87 PSIG)
Slope	59 \pm 3 at 25°C
Zero Point	7pH
Asymmetry Potential	\pm 25mV
Body Type	PC (Polycarbonate)
Reference	Ag/AgCl
No. of Junction	Single
Membrane impedance	< 200m Ω at 25°C
Membrane Shape	Spherical
Electrode Diameter	29.5 mm (1.16"), with 3/4" NPT thread at ends
Standard Electrode Cable Length	5 m (16.4 ft) Low Noise Coaxial Cable

Online pH Electrode

Catalog No. 101104

Disclaimer

The Products details given on this page are indicative in nature and JAPSON reserves the right to change them without prior notice. Buyer is also requested to re-check the specifications and other features of product at the time of order as product development is a continuous process and minor modifications may be made to design based on latest availability, process and design.